

SOLCEM

Solwalseal

DESCRIPTION

SOLWALSEAL provides clear, water repellent protection to exterior surfaces, such as concrete, stone, brick and paving. It also binds together surface particles producing a toughened, self-cleaning finish.

APPLICATION

- Surfaces should be sound, clean, dry to the touch, and free of cracks and all traces of contaminants.
- Apply by wide soft brush, roller or spray.
- Best results will be obtained by a low pressure airless sprayer.
- Firstly a light mist coat should be applied, followed by a heavy flood coat within 20 to 30 minutes whilst the first coat is still tacky, followed by another if required, again whilst the surface is still tacky.
- Optimum performance will be obtained when the surface will absorb no further material.
- Treatment should not be undertaken in freezing temperatures.
- The treated surface should be protected from rain for at least 30 minutes following final application.

COVERAGE

Depending upon surface absorbency, 1 litre will cover 6-8m² as a mist coat and 3-4m² as a flood coat.

STORAGE

Store in a tightly closed container in a cool, well ventilated area away from sources of ignition (including lighting and electrical equipment). Prevent the build up of electrostatic charge in the immediate area.

HEALTH & SAFETY

- Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Drench the affected skin with running water for 10 minutes or longer if substance is still on skin. Consult a doctor.
- Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.
- Ingestion: Wash out mouth with water. Do not induce vomiting. If conscious, give half a litre of water to drink immediately. Consult a doctor.
- Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.
- Reference should be made to the separate SOLWALSEAL Health & Safety sheet.

