

# Concrete Snake Spacer

Bluebay Concrete Snake Spacers are manufactured from extruded fibrous concrete with a minimum concrete Strength of 50N/mm<sup>2</sup>. Manufactured in accordance with BS7973-1 :2001. The snake spacers have a high tensile strength and stability when they are installed diagonally to the reinforcement.



Product Code	Cover (mm)	Length (mtr)	Pallet Size (no)	Pallet Weight (kg)
CSS9025	25	0.9	1000	1020
CSS9030	30	0.9	800	1150
CSS9035	35	0.9	500	1170
CSS9040	40	0.9	300	1050
CSS9050	50	0.9	250	1080
CSS9060	60	0.9	150	1050
CSS9075	75	0.9	100	1050
CSS90100	100	0.9	60	1030

<b>Compression Strength</b>	≥ 50N/mm <sup>2</sup> (Satisfied to BS7973 PT1-2)
<b>Water Penetration</b>	≤ 3mm
<b>Height / Cover Accuracy</b>	+/- 2mm on cover 25 - 60mm
<b>Height / Cover Accuracy</b>	+/- 3mm on cover 75 - 100mm
<b>Raw Materials</b>	CEM I 52.5 N, Calcium Carbonate, PFA, Concrete Sand
<b>Reinforcing</b>	Polypropilene Fibres, Polyester Threads
<b>Slump</b>	S1 0 - 3cm

Note: In the absence of a specific harmonised European standard (hEN) or European Technical Approval (ETA), a CE Mark is not required.