



Never compromise on quality!



FLASHING TAPE

High Performance Self-Adhesive Flashing



BITUBOND BITUMEN SOLUTIONS & COMPOUNDS RANGE

Description:

A crease resistant lead coloured flashing tape for general repairs and sealing. It has a heavy duty aluminium/polyester laminate facing with a high grade bitumen backing. This gives the product tear resistance, thus aiding speed and ease of application.

Uses

Bond It **FLASHING TAPE** is designed for use as flashing on flat and pitched roofs, on parapets and chimney stacks. It is also exceptional for sealing around RSJ's, flues, concrete columns, rooflights, guttering and extractor vents. The strength of the facing gives resistance to puncturing and the bitumen gives flexibility and adhesion but without the problems of slump.

- ♦ Replacement & repair of flashings.
- ♦ Repair & sealing of down pipes.
- ♦ Sealing glazing & roof lights.
- ♦ Sealing parapets.
- ♦ Waterproofing of coping & roof ridges.
- ♦ General roof repairs.

On New Building: Bond It **FLASHING TAPE** can be used in the following application: as flashing on flat or pitched roofs of asbestos, concrete or aluminium, parapet flashing, sealing upstands through roofs. Sealing around RSJ's, flues, concrete columns, rooflights and extractor vents. Sealing joints of pipes of different materials prior to casting in concrete. Vertical DPC for sealing cavity walls at door and window openings. Capping corrugated roof ridges prior to fixing ridge flashing. Protection of stool stanchions at contact with facing bricks. Damp-proof membrane to columns, protection of pipes and general insulation work.

On Repair Work: Repairing damaged lead flashing and lead roofing. Sealing mortar faults. Repair to damaged slates and tiles in awkward situations. Downpipe and joint repairs. Gutter and valley linings and joint repairs on asbestos, concrete or metal. Gutter closures to prevent storm overflow into buildings. Eaves closure. Drip tray into gutters. Glazing bars, rooflights and northlights. Cappings to asbestos roofing. Emergency repairs to windows. Sealing leaks in cars, trucks and vans, etc.

Sizes

Bond It **FLASHING TAPE** is available in 10 metre rolls and in widths of 50, 75, 100, 150, 225, 300, 450 and 600mm. It is also available in 3 metre rolls in widths of 100, 150 and 225mm.

Composition

Bond It **FLASHING TAPE** comprises heavy-duty facing coated with a

minimum 1.2mm thickness of pressure sensitive modified bitumen. The adhesive content is specially formulated for flexibility at low temperatures and resistance to flow at high temperatures and an immediate bond is obtained by applying firm hand pressure. The strength of the bond increases with time. The thickness of the self-adhesive bitumen ensures very close contact, even on comparatively rough surfaces, while the product's durability provides long-lasting protection combined with an attractive appearance.

Supplied in rolls for fast and clean application and conforms readily to awkward contours, providing excellent weather protection. It can be used for all flashing and roofing applications and general water sealing repairs on masonry, asbestos, timber, metal or glass. No special skills or tools are required.

Preparation

All surfaces must be structurally smooth, clean, dry and dust-free. Any loose matter must be removed with a wire brush. Any moss or lichen should be removed using a fungicidal wash such as Bond It **MOULD STOP**. Porous or rough surfaces should be primed with **BITUMEN PRIMER** and allowed to dry before applying **FLASHING TAPE**.

In very cold weather Tape should be stored indoors in warm (18°C+) conditions overnight before use.

Application

1. Cut a section of **FLASHING TAPE** to the required length, remove the release paper and press down the adhesive bitumen to the previously prepared surface.
2. Ensure full contact by smoothing down with a cloth, taking care to eliminate air bubbles.
3. Roll down the edges with a wall paper roller or trowel to make a good edge seal. Take care to avoid damaging the **FLASHING TAPE** surface.
4. Joined sections of **FLASHING TAPE** should always be overlapped by a minimum of 25mm (one inch) and well rolled down.



Note: in cold weather adhesion will be improved by storing the roll in a warm room for 12 hours or more before use, or by gently warming the backing strip during application.

DO NOT UNDER ANY CIRCUMSTANCES APPLY IN CONDITIONS BELOW 5°C. Not suitable for polycarbonate or acrylic glazing e.g. conservatory roofs.

Storage

Store in a cool dry place. In very cold weather the flashing may be softened by gentle application of air using a warm air gun. DO NOT USE NAKED FLAMES.

Health & Safety

Please refer to separate material safety data sheet for full handling, use and storage instructions. Keep out of reach of children. It is the users responsibility to determine suitability for use. If in doubt contact our Technical Department for advice.

Note: this information is for general guidance only, since site conditions and labour are beyond our control. It is recommended that users make their own tests to determine suitability.

Product Details:

Size:	50mm x 10m	75mm x 10m	100mm x 10m	150mm X 10m
Colour:	Grey	Grey	Grey	Grey
Code:	BDF001	BDF002	BDF003	BDF004
Barcode:	5060021360984	5060021360991	5060021361004	5060021361011

Size:	225mm x 10m	300mm x 10m	450mm x 10m	600mm X 10m
Coverage:	Grey	Grey	Grey	Grey
Code:	BDF005	BDF006	BDF007	BDF008
Barcode:	5060021361028	5060021361035	5060021367648	5060021367655

Size:	100mm x 3m	150mm x 3m	225mm x 3m
Coverage:	Grey	Grey	Grey
Code:	BDF009	BDF010	BDF011
Barcode:	5060021361738	5060021361745	5060021361752

The data presented in this leaflet are in accordance with the present state of our knowledge, but do not absolve the user from carefully checking all supplies immediately on receipt. We reserve the right to alter product constants within the scope of technical progress or new developments. The recommendations made in this leaflet should be checked by preliminary trials because of conditions during processing over which we have no control, especially where other companies raw materials are also being used. The recommendations do not absolve the user from the obligation of investigating the possibility of infringement of third parties rights and, if necessary clarifying the position. Recommendations for use do not constitute a warranty, either expressed or implied, of the fitness or suitability of the products for a particular purpose.



Part of the Bond It Bitubond Range



Certificate Number:
6152
ISO 9001
ISO 14001; ISO 45001



BOND IT
Head Office: Unit G16 River Bank Way, Lowfields Business Park,
 Elland, West Yorkshire HX5 9DN.
 Telephone: +44 (0)1422 315300 Fax +44 (0)1422 315310
 Email: salesuk@bonditgroup.com Website: www.bonditgroup.com



V3 27/02/17
 Supersedes: V2 15/07/14