

Continuous Plastic Spacer (Drupak)

Description

Extra strong spacer with large supporting area used for horizontal reinforcement. Made of 100% high quality recycled PE. Very good concrete flow by large cut outs at the side and on top. Suitable for fair faced concrete and prefabricated ceiling.

Drupak comes in a 2mt profile but has the opportunity to be placed in 1mt lengths thanks to a special clip that has been designed for ease of handling on site. Drupak spacer comes in two variants:



Sizing & Packing

Product Code	Concrete Cover (mm)	Length (mt)	Pack (mt)	Pallet (mt)
Drupak 1 - Width 36mm				
CPS/DP1/15/2	15	2	100	6000
CPS/DP1/20/2	20	2	100	6000
CPS/DP1/25/2	25	2	100	5400
CPS/DP1/30/2	30	2	100	5400
CPS/DP1/35/2	35	2	60	4800
CPS/DP1/40/2	40	2	60	4320
CPS/DP1/50/2	50	2	60	4320
Drupak 2 - Width 46mm				
CPS/DP2/25/2	25	2	100	4500
CPS /DP2/30/2	30	2	100	4500
CPS/DP2/35/2	35	2	60	3900
CPS/DP2/40/2	40	2	60	3600
CPS/DP/45/2	45	2	60	3000
CPS/DP2/50/2	50	2	60	3000

Specification

Requirement	Description	Result
6.2	Min 25% Voids	Pass
7.3	+ - 2mm Tolerance	Pass
7.72	Breadth / Height Ratio	Pass
9	Max deflection of 1mm Under 0.5kn test load	Pass
11	Marking of packs	Pass



In accordance with the requirements of 'Spacers and chairs for steel reinforcement and their specification' the above products have been supplied and comply with the requirements of British Standard BS7973-1:2001

Note: In the absence of a specific harmonised European standard (hEN) or European Technical Approval (ETA), a CE Mark is not required.

Unit 51, Portmanmoor Road Ind Est,
Ocean Park, Cardiff, CF24 5HB