

# Solbond Acrylic Primer

## Description:

Solbond Acrylic Primer is a single component polymer emulsion system designed as bonding agents and curing membranes for repair products. It may also be used as concrete surface sealers in non-traffic areas. Solbond Acrylic Primer is recommended as a primer for cementitious repair systems. Solbond Acrylic Primer is also recommended as a curing membrane for repairs. It may also be used as an economical dust proofer for non-trafficked cementitious surfaces.

## Application:

- Solbond Acrylic Primer is supplied ready for use when used as bonding primers or curing membranes.
- When used as a surface sealer, Solbond Acrylic Primer should be diluted 1:1 with water for the first coat and as supplied for the second coat.
- The application should be by spray, brush, or medium pile roller.
- Care should be taken to ensure complete and thorough wetting of the surface.

## Coverage & Yield:

- **As a Primer:** 4-6m<sup>2</sup>/litre.
- **As a Curing Membrane:** 6-8m<sup>2</sup>/litre.
- **As a Surface Sealer:** 6-10m<sup>2</sup>/litre.

## Storage:

- Store in dry conditions between +5°C and +25°C.
- Shelf life is 12 months if stored in dry conditions.
- Protect from frost.
- Do not use when the temperature is below 5°C and falling.



- **Single component: No site mixing.**
- **Easy to use: Ready to use straight from the container.**
- **High bond strength: Excellent bond strength between systems and concrete.**
- **Cost effective: Economical in use.**
- **Curing aid: Can be used as a curing membrane.**

### Pack Size

5lt Bottles & 25lt Drums