

## Dywidag Plastic Cones

### Application:

When installing wall formwork the Dywidag Plastic Cones are designed to be used on both ends of the Dywidag ID Form sleeve giving 10mm cover allowing easy extraction of the formtie. The plastic cone can easily be removed leaving a tapered finish that allows easy grouting and correct cover.

Solplug Tie Hole filler is also available

### Material:

- Polyolefin (PO)
- Free of CFC, HFC
- Without substances of very high concern according to the candidate list of ECHA (REACH Regulation)

### Packaging:

Free of halogen-containing compounds, azo dyes, flame retardants.

### Order information:

| Item-No. | For Tube Ø mm | Fitting Length mm | Pcs/ Bag | Pcs/ Pallet |
|----------|---------------|-------------------|----------|-------------|
| K20      | 20            | 10                | 500      | 24.000      |
| K22*     | 22            | 10                | 500      | 30.000      |
| K26      | 26            | 10                | 250      | 28.000      |
| K32      | 32            | 10                | 500      | 5.000       |

Standard Cone



| Item-No. | For Tube Ø mm | Fitting Length mm | Pcs/ Bag | Pcs/ BigBag | Pcs/ Pallet |
|----------|---------------|-------------------|----------|-------------|-------------|
| K22/2    | 22            | 20                | 250      | 1.000       | 25.000      |
| K22/3    | 22            | 30                | 250      | 1.000       | 5.000       |
| K22/5    | 22            | 50                | 250      | -           | 8.000       |
| K26/5    | 26            | 50                | 125      | 500         | 15.000      |

Recessed Cone



Note: In the absence of a specific harmonised European standard (hEN) or European Technical Approval (ETA), a CE Mark is not required.

Unit 51, Portmanmoor Road Ind Est,  
Ocean Park, Cardiff, CF24 5HB